



HOUSE OF REPRESENTATIVES

H. No. 1061

BY REPRESENTATIVES YAP (V.), MADRONA, UNGAB, SAVELLANO AND
COJUANGCO

AN ACT CONVERTING THE STA. IGNACIA-GUIMBA
PROVINCIAL ROAD IN THE PROVINCES OF
TARLAC AND NUEVA ECIJA VIA GERONA-PURA
ROAD STRETCHING FROM BARANGAY NAMBALAN,
MUNICIPALITY OF STA. IGNACIA TO BARANGAY
BUENAVISTA, MUNICIPALITY OF PURA, ALL IN THE
PROVINCE OF TARLAC INTO A NATIONAL ROAD
AND APPROPRIATING FUNDS THEREFOR

*Be it enacted by the Senate and House of Representatives of the Philippines in
Congress assembled:*

1 SECTION 1. The Sta. Ignacia-Guimba Provincial Road in
2 the provinces of Tarlac and Nueva Ecija via Gerona-Pura Road
3 stretching from Barangay Nambalan, Municipality of Sta. Ignacia
4 to Barangay Buenavista, Municipality of Pura, all in the Province
5 of Tarlac is hereby converted into a national road.

1 SEC. 2. The technical description of the road is as follows:

TECHNICAL DESCRIPTION		
LINE	BEARING	DISTANCE
1-2	N 67-16 E	2689.578
2-3	N 68-41 E	35.392
3-4	N 71-38 E	26.708
4-5	N 73-15 E	25.022
5-6	N 79-10 E	13.757
6-7	N 83-53 E	32.816
7-8	N 88-02 E	59.318
8-9	N 89-19 E	4705.801
9-10	S 85-53 E	27.050
10-11	S 66-58 E	121.278
11-12	S 52-39 E	2326.539
12-13	S 43-57 E	68.795
13-14	S 40-29 E	27.129
14-15	S 47-28 E	19.706
15-16	S 64-25 E	16.646
16-17	S 79-22 E	30.854
17-18	S 89-33 E	568.825
18-19	N 81-52 E	29.323
19-20	N 76-05 E	36.970
20-21	N 71-19 E	40.885
21-22	N 67-15 E	649.792
22-23	N 69-51 E	24.893
23-24	N 77-07 E	15.722
24-25	N 82-29 E	24.930
25-26	S 82-41 E	27.333
26-27	S 75-53 E	20.754
27-28	S 75-31 E	1101.441
28-29	S 83-29 E	35.415
29-30	S 87-59 E	42.729
30-31	N 86-14 E	19.235
31-32	N 75-19 E	92.526
32-33	N 75-22 E	1433.414
33-34	N 69-57 E	22.143
34-35	N 69-46 E	20.475
35-36	N 68-44 E	65.590
36-37	N 68-37 E	314.871

TECHNICAL DESCRIPTION		
LINE	BEARING	DISTANCE
37-38	N 68-39 E	394.289
38-39	N 69-18 E	391.769
39-40	N 63-58 E	564.084
40-41	N 61-46 E	61.242
41-42	N 67-55 E	61.891
42-43	N 66-51 E	91.814
43-44	N 60-32 E	91.045
44-45	N 57-28 E	33.361
45-46	N 77-24 E	43.170
46-47	N 82-38 E	41.561
47-48	S 87-57 E	17.616
48-49	N 81-54 E	37.719
49-50	N 77-17 E	73.091
50-51	N 66-45 E	84.697
51-52	N 57-40 E	131.877
52-53	N 57-19 E	91.371
53-54	N 59-07 E	114.844
54-55	N 62-02 E	56.980
55-56	N 64-52 E	321.447
56-57	N 63-13 E	593.772
57-58	N 62-39 E	164.312
58-59	N 66-44 E	90.613
59-60	N 70-39 E	33.570
60-61	N 70-25 E	62.762
61-62	N 83-12 E	92.622
62-63	N 84-20 E	527.944
63-64	N 84-14 E	34.076
64-65	N 78-45 E	68.746
65-66	N 76-56 E	32.367
66-67	N 73-27 E	340.124
67-68	N 73-00 E	93.017
68-69	N 72-18 E	2221.902
69-70	N 74-36 E	95.189
70-71	N 78-02 E	148.577
71-72	N 68-19 E	63.100
72-73	N 60-18 E	63.198
73-74	N 64-24 E	1008.345

TECHNICAL DESCRIPTION		
LINE	BEARING	DISTANCE
74-75	N 63-59 E	607.729
75-76	N 64-15 E	1300.409
76-77	N 64-16 E	480.245
77-78	S 25-44 E	20.000
78-79	S 64-16 W	480.238
79-80	S 64-15 W	1300.363
80-81	S 63-59 W	607.755
81-82	S 64-24 W	1007.700
82-83	S 60-18 W	63.885
83-84	S 68-19 W	66.204
84-85	S 78-02 W	149.676
85-86	S 74-36 W	94.187
86-87	S 72-18 W	2221.622
87-88	S 73-00 W	93.217
88-89	S 73-27 W	40.811
89-90	S 76-56 W	33.292
90-91	S 78-45 W	70.021
91-92	S 84-14 W	35.053
92-93	S 84-20 W	527.763
93-94	S 83-12 W	90.888
94-95	S 74-25 W	60.568
95-96	S 70-39 W	32.227
96-97	S 66-44 W	89.214
97-98	S 62-38 W	163.698
98-99	S 63-13 W	594.162
99-100	S 64-52 W	321.239
100-101	S 62-02 W	55.975
101-102	S 59-07 W	114.021
102-103	S 57-19 W	91.120
103-104	S 57-40 W	133.528
104-105	S 66-45 W	88.129
105-106	S 77-17 W	75.739
106-107	S 81-54 W	40.300
107-108	N 87-57 W	17.747
108-109	S 82-38 W	39.002
109-110	S 77-24 W	38.741
110-111	S 57-28 W	330.381

TECHNICAL DESCRIPTION		
LINE	BEARING	DISTANCE
111-112	S 60-32 W	92.683
112-113	S 66-51 W	93.104
113-114	S 67-55 W	61.004
114-115	S 61-46 W	60.550
115-116	S 63-58 W	565.401
116-117	S 69-18 W	392.587
117-118	S 68-39 W	394.161
118-119	S 68-37 W	314.894
119-120	S 68-44 W	65.791
120-121	S 69-46 W	20.686
121-122	S 69-57 W	23.121
122-123	S 75-22 W	1434.345
123-124	S 75-19 W	94.437
124-125	S 86-14 W	22.155
125-126	N 87-59 W	44.525
126-127	N 83-29 W	37.596
127-128	N 75-31 W	1102.771
128-129	N 75-53 W	19.502
129-130	N 82-41 W	23.541
130-131	S 82-29 W	21.388
131-132	S 77-07 W	13.514
132-133	S 69-51 W	23.169
133-134	S 67-15 W	650.047
134-135	S 71-19 W	42.429
135-136	S 76-05 W	38.813
136-137	S 81-52 W	31.833
137-138	N 89-33 W	572.110
138-139	N 79-22 W	35.262
139-140	N 64-25 W	22.249
140-141	N 47-28 W	23.906
141-142	N 40-29 W	27.744
142-143	N 43-57 W	66.667
143-144	N 52-39 W	2322.506
144-145	N 66-58 W	115.434
145-146	N 85-53 W	22.879
146-147	S 89-19 W	4704.740
147-148	S 88-02 W	58.372

TECHNICAL DESCRIPTION		
LINE	BEARING	DISTANCE
148-149	S 83-53 W	31.268
149-150	S 79-10 W	11.899
150-151	S 73-15 W	23.705
151-152	S 71-38 W	25.912
152-153	S 68-42 W	34.632
153-154	S 67-17 W	2689.330
154-0	N 22-43 W	20.00

1

2 SEC. 3. The Secretary of Public Works and Highways shall
3 include in the Department's program the improvement, repair and
4 maintenance of the said road, the funding of which shall be included
5 in the annual General Appropriations Act.

6 SEC. 4. This Act shall take effect fifteen (15) days after its
7 publication in the *Official Gazette* or in a newspaper of general
8 circulation.

Approved,

O